



PRODUCT INFORMATION

dexos1™ FULL SYNTHETIC OIL «EXTRANOL» 5W-20

Overview

dexos1 5W-20 FULL SYNTHETIC motor oil is specifically formulated for and licensed by General Motors to meet their new Global Engine Oil Specification. The product is manufactured using synthetic base oils and advanced additive technology which exceeds the requirements of the General Motors specification. This oil meets or exceeds the latest API SN and ILSAC GF-5 specifications as well as all previous service classifications API SM, SL and ILSAC GF-4 and GF-3. This oil is a premium quality motor oil designed to meet the most demanding lubrication requirements of today's naturally aspirated, turbocharged and super-charged gasoline fueled engines. This oil is specially formulated to provide excellent oxidation stability, increase wear protection, excellent low temperature flow properties, reduce oil consumption and enhance fuel economy.

Features and Benefits

- Formulated for superior engine protection
- Extremely low volatility
- Excellent Oxidation Stability
- Excellent protection against sludge and varnish
- Highly resistant to foaming and corrosion
- Improves oil film strength and breakdown resistance.

Recommended For Applications

API SN
ILSAC GF-5
GM 6094M
GM 4718M
Ford M2C153H
M2C929-A
Daimler Chrysler 10796
MS 6395M

TYPICAL PROPERTIES

PRODUCT CODE 597

PROPERTY	5w-20 dexos1™
CCS, cP (@ -30°C)	4900
Viscosity, cSt @ 100°C	8.71
Viscosity, cSt @ 40°C	51.3
Viscosity Index	148
Flash Point, °C	204
Pour Point, °C	-43
Phosphorous, Wt. (%)	0.074
Zinc, Wt. (%)	0.084
Calcium, Wt. (%)	0.206
NOACK, Wt. (%)	12
HT/HS, Cp @150°C	2.6

MADE IN USA.

www.extranol.com
info@extranol.com