



PRODUCT INFORMATION

dexos1™ FULL SYNTHETIC OIL «EXTRANOL» 5W-30

Overview

FULL SYNTHETIC motor oil dexos1™ 5W-30 is designed to meet or exceed the requirements specified for gasoline fueled GM vehicles produced after 2011. This premium synthetic motor oil is produced with a proprietary blend of high performance synthetic base stocks along with a proprietary component system licensed and approved by general motors. This fluid is designed to perform under extreme conditions where excellent cold temperature properties and thermal breakdown resistance are required. The oil also exceeds the performance requirements of ILSAC GF-5 fluids.

Features and Benefits

- Formulated for superior engine protection
- Extremely low volatility
- Excellent Oxidation Stability
- Excellent protection against sludge and varnish
- Highly resistant to foaming and corrosion
- Improves oil film strength and breakdown resistance.

Recommended For Applications

API SN
ILSAC GF-5
GM 6094M, 4718M
FORD MCC153H, M2C929-A

TYPICAL PROPERTIES

PRODUCT CODE 593

PROPERTY	5w-30 dexos1™
CCS, cP(@ -30°C)	4900
Viscosity, cSt @ 100°C	11,0
Viscosity, cSt @ 40°C	63,0
Viscosity Index	165
Flash Point, °C	220
Pour Point, °C	-45
NOACK, Wt. (%)	11
HT/HS, Cp @150°C	3,1

MADE IN USA.

www.extranol.com

info@extranol.com