



## PRODUCT INFORMATION

### SYNTHETIC BLEND MOTOR OIL «EXTRANOL» 5w-30 GF-5

#### Overview

SYNTHETIC BLEND PASSENGER CAR ENGINE OIL «EXTRANOL» 5w-30 GF-5 are specially formulated using synthetic and Group II base oils and high performance additive packages to provide superior performance in gasoline fueled and flex-fueled engines.

These oils are formulated for excellent oxidation stability and low temperature properties to insure protection during cold starts.

EXTRANOL PREMIUM SYNTHETIC BLEND GF-5 engine oils exceed the requirements of ILSAC GF-5 and are "Resource Conserving" for improved fuel economy.

#### Features and Benefits

- Uniquely formulated proven to help extend engine life
- Proven protection against sludge and engine wear
- Helps prevent the formulation of sludge and harmful deposits
- Contains frictional reducing additives
- Certified as API SN / Resource Conserving

#### Recommended For Applications

ILSAC GF-5

API SN, SM, SL, SJ

Ford WSS-M2C946-A

Ford WSS-M2C949-A

GM 6094M

#### TYPICAL PROPERTIES

PRODUCT CODE 591

PROPERTY	Extranol 5w-30 Syn blend
Viscosity, cSt @ 40°C	67.0
Viscosity, cSt @ 100°C	10.8
CCS, cP( @ -30°C)	6000
Viscosity Index	160
Flash Point, °C	195
Pour Point, °C	-41
Phosphorous, Wt. (%)	0.077
Zinc, Wt. (%)	0.085
NOACK, Wt. (%)	14.5
HT/HS, Cp @150°C	3.0

MADE IN USA.

[www.extranol.com](http://www.extranol.com)

[info@extranol.com](mailto:info@extranol.com)