



PRODUCT INFORMATION

EXTRANOL TRACTOR HYDRAULIC FLUID

Overview

EXTRANOL TRACTOR HYDRAULIC FLUID is a premium, exceptional high quality universal tractor hydraulic fluid for use in transmissions, final drives and hydraulic systems of all major brands of tractors and other farm equipment using a common fluid reservoir.

This fluid incorporates the latest additive chemistry to provide maximum protection for all systems requiring a universal fluid.

Features and Benefits

Enhanced frictional properties that optimize clutch and PTO performance and improve wet brakes and PTO chatter control. (Power Take-Off).

Compatible with latest clutch materials and elastomers resulting in longer clutch life and reduced leakage. High viscosity index and shear stability causing consistent operating response.

Excellent protection against rust, corrosion, yellow metal etching, low temperature properties, strong anti-wear, extreme pressure properties, thermal and oxidation stability.

Multipurpose capability in simplifying inventory by reducing misapplication problems.

Applications

Heavy duty transmissions, differentials, final drives, hydraulic systems, power steering systems, wet brakes, PTO's and hydrostatic drives. Top-up and re-fill of systems. Commercial transmission applications requiring Type A (Suffix A), Dexon and Type F fluids. Do not use in passenger car automatic transmissions.

Typical Properties

PRODUCT CODE 441

Viscosity, cSt @ 40°C 59.5

Viscosity, cSt @ 100°C 9.25

Viscosity, cP @ -20°C 4500

Viscosity, cP @ -35°C 49000

Viscosity Index 150

Pour Point, °F -44

Flash Point, °F 432

Sulfated Ash, wt% 1.48

Total Base Number 10.1

Zinc, wt% 0.157

MADE IN USA.

www.extranol.com

info@extranol.com