



PRODUCT INFORMATION

EXTRANOL FULL SYNTHETIC DIFFERENTIAL GEAR OIL 75w-90

Overview

EXTRANOL FULL SYNTHETIC DIFFERENTIAL GEAR OIL 75w-90 is a full synthetic, premium quality, commercial drive-train lubricant designed to meet the rigorous demands of extended drain warranty requirements. It provides outstanding performance in heavy duty drive-trains where extreme pressure and shock loading are common. Formulated for extreme cleanliness and superior thermal stability under severe conditions, this oil also offers enhanced friction reduction properties and exceptional shear stability.

Features and Benefits

- Exceptional thermal stability
- Resistance to high temperature oxidation
- Extend gear and bearing life to minimum deposits and longer seal life.
- Outstanding protection against low speed/high torque-wear and high speed scoring.
- Retains viscosity and film strength under severe operating conditions
- Exceptional shear-stability.
- Compatible with typical automotive seals and gaskets
- Excellent rust, staining, and corrosion protection of copper and its alloys.

Recommended For Applications

- Eaton Roadranger (E500)
- ArvinMeritor extended warranties of 750,000 miles with oil drains of 500,000 miles.
- Mack GO-J and GO-J Plus (75W90) extended service classifications.

Applications

- Heavy-duty manual transmissions, axles and final drives requiring API GL-5 and MT-1 performance.
- Off-highway light and heavy-duty trucks, busses and vans.
- Includes hypoid and worm gears operating under conditions where high speed/high torque conditions prevail.
- Equipment such as winch reduction gears and crawler vehicle propulsion gear drives that are exposed to severe low temperatures.

Typical Properties

- PRODUCT CODE 633
- SAE Grade 75w-90
- Viscosity, cSt @ 100°C 15.0
- Viscosity, cSt @ 40°C 101
- Pour Point, °C -41
- Flash Point, °C 205
- Density @ 15C 0.866
- Foam Sequence I, II, II D892 Pass

MADE IN USA.

www.extranol.com
info@extranol.com