



PRODUCT INFORMATION

EXTRANOL FULL SYNTHETIC DIFFERENTIAL GEAR OIL 80w-140

Overview

EXTRANOL SYNTHETIC DIFFERENTIAL GEAR OIL 80w-140 is a full synthetic, premium quality, commercial drivetrain lubricant designed to meet the rigorous demands of extended drain warranty requirements. It provides outstanding performance in heavy duty drivetrains where extreme pressure and shock loading are common. Formulated for extreme cleanliness and superior thermal stability under severe conditions, this oil also offers enhanced friction reduction properties and exceptional shear stability.

Features and Benefits

- Extended drain interval
- Excellent EP properties
- Superior thermal stability
- Exceptional Shear stability

Typical Properties

PRODUCT CODE 634
SAE Grade 80w-140
Viscosity, cSt @ 100°C 26
Viscosity, cSt @ 40°C 225
Pour Point, °C -36
Flash Point, °C 210
Density @ 15C 0.870
Foam Sequence I, II, II D892 Pass
API GL-5 / MT-1 X
Scania STO 1:0 X
Eaton Roadranger (E500) X
Mack GO-J plus X
Mack GO-J X
ArvinMeritor O-76N X
International TMS-6816 X
SAE J2360 X
MIL-PRF-2105E X

MADE IN USA.

www.extranol.com
info@extranol.com